

### Superior Air Performance

#### Standard Construction

##### Frame

1.5" x .063" (38 x 1.6) Extruded Aluminum (6063-T5)

##### Blades

.125"(3.2) Extruded Aluminum (6063-T5) 1"(25) blade spacing

##### Finishes

MILL

##### Minimum Size

6" W x 5 13/16" H (152 x 148)



##### Maximum Size

72" W x 72" H (1829 x 1829)



#### Available Options

- Extended Sill (loose) 14 GA. Aluminum
- Blank-off Panels: Aluminum or Galvanized, Insulated or Non-Insulated
- Formed Flange and Mounting Angle up to 4"
- Birdscreen: Aluminum or Galvanized
- Insect Screen: Aluminum or Bronze
- Finishes: Prime Coat, Baked Enamel, Duranar, Duranar XL
- Anodized Finishes: Clear or Colour (Light Bronze, Medium Bronze, Dark Bronze, Black)



<b>PROJECT</b>				<b>CUSTOMER</b>			
<b>ARCHITECT</b>				<b>ENGINEER</b>			
<b>SPEC. SYMBOL</b>				<b>DATE</b>			
QTY	TAG	LOUVER SIZE		OPENING SIZE		OPTIONS	UNITS: <input type="checkbox"/> IMPERIAL <input type="checkbox"/> METRIC
		WIDTH	HEIGHT	WIDTH	HEIGHT		